

TECHNICAL DATASHEET

TUBELED 1200MM 20W G13 DOUBLE T8

06-10-2020



VO/TUBELED/20W/G13/6500K/1200MM/DOUBLE/T8 LED TUBE

NOTES

General Informations

Stock Code	1600750
HSC/GTIP Code	8543.70.90.00.19
EAN-13 (Inbox Barcode)	6972538041913
ITF-14 (Outbox Barcode)	16972538041910
Introduction	Double ended

Electrical Characteristics

Current Type	AC
Operation Voltage	165-265 Volt
Operation Frequency	50/60 Hertz
Electrical Current	0,16 Amper
Power	20 Watt
Power Factor	>0.6
Luminous Efficiency	96 lumen/Watt
Energy Savings	0,83
Dimmable	No
Electrical Protection Class	Class II

Electrical Component Specifications

Component Fitting Type	External Driver
Driver Properties	IC
Driver Input Voltage	165-265 Volt
Driver Input Current	0,16 Amper

Lighting Characteristics

Luminous Flux	1920 lumen
Time for 60% of Lumen	<0.6 seconds
Light Beam Angle	320°
Flicker	No
LED Type	SMD

Mechanical Parameters

Bulb Body Shape	T8
IP Protection Class	IP20
Switch On/Off Cycle	30000
Lifetime	25000 hours
Body Material	Glass Powder
Body Colour	White
Diffuser Material	Glass with powder
Product Height	1213 millimeter
Product Width	Ø28 millimeter
Ambient Temperature (Ta)	-20°C<Ta<40°C

Logistic Informations

Inbox Length	15 millimeter
Inbox Width	18 millimeter
Inbox Height	1245 millimeter
Outbox Length	1245 millimeter
Outbox Width	210 millimeter
Outbox Height	165 millimeter
Outbox Volume	0,04313925 m ³
Outbox Quantity	30 pieces
Unit Net Weight	0,203 kilogram
Outbox Net Weight	6,1 kilogram
Outbox Gross Weight	6,7 kilogram

IMPORTANT NOTES: VITO reserves the right to change/remove models or specifications partially/completely without any notice. Information, models and photographs of the products in this technical datasheet can not be used, reproduced or republished without permission. However, some parts can be quoted by giving reference and/or chapter number belonging to technical datasheet. Most of the items in the datasheet have been designed by our company within indicated technical specifications inside. Our company is not responsible for errors caused by wrong installation and operating against rules according to qualifications specified in the product details. Photographs printed in this datasheet may not reflect the actual color of the product depending on printing conditions. In the same context, typographical errors may possibly be found in the texts.