

Product Data Sheet

ELECTRICAL EQUIPMENT

UNICO-4 3680 MAX.W

CODE: **8002510**



Area of application

Multisockets with Child-Protection Shutter, Switch and USB source.
For safety electrical connection to be used for indoor applications only.

Product Advantages

UNICO is a unique group socket with switch, made by PP. Is equipped with cable type H05VV-F and offers maximum load of 16A - 3680W. The insulation of the cable is PVC. All VITO group sockets are equipped with protection against direct contact. Input :250 Vac ,50 Hz ,0,25 A Max .
Output : USB - A :5,0 Vdc ,2,4 A ;
USB - C :5,0 Vdc ,3,0A;
USB - A + C :5,0 Vdc ,3,1A,15,5 W Max .(in total)

Product Data Sheet

ELECTRICAL EQUIPMENT

UNICO-4 3680 MAX.W

CODE: **8002510**

Product Features

Electrical

Power (Watt): 3680 MAX.

Voltage: Max. 250V AC ~ 16A

Power Factor: --

Electrical Protection: Class I

Surge Protection: --

Dimmability: --

Switch Cycle (Times): --

Material Characteristics

IP Class: IP20

IK Class: -

Material: PP

Ambient Temperature: --

Body Color: WHITE

Product Size (mm):

Technical Drawing

Lighting

Lumen (Lm): --

Luminaire efficacy (Lm/W): --

Colour Temperature: --

Beam Angle: --

CRI: Ra --

Lifetime (Hours): --

EEL : --

Packing Informations

Pieces/Outbox: 20

Outbox Size (mm): 510x360x180

Outbox G.W. (Kg): 12,05

Outbox Volume (m³): 0,033

Unit Weight (Gr): 602,5

Barcode : 6972538041043

Light Distribution Curve

System Definition: VT/UNICO-4/3M 3G1.5 CABLE/SWITCH/USB/WHT/M SOCKET

VITO EUROPE

102 Iztochna Tangenta str. 4th Floor

P.C. 1528, Sofia/Bulgaria

Phone: +359 2 4341575

E-mail: info@vitoeurope.com

www.vitolighting.com